



INSTALLATION GUIDE:
LACQUERED WOOD
FLOORING

INSTALLATION GUIDELINES FOR LACQUERED WOODEN FLOORS

LACQUERED - WHAT IS IT?

Lacquered or varnished floors are extremely easy to deal with as the hard coating is a combination of anti-scratch properties as well as elastic layers (overall 5-7 layers if factory finished – onsite finishing installers normally apply only three coats) which provide great resistance against the day-to-day activities.

With simply precautions and maintenance, a varnished floor will stay beautiful for a long time. Should damage occur, individual boards can be substituted and if required (please only use experienced installers to perform this job). After prolonged usage and wear and tear, the floor can be sanded and a new coating can be applied. A new varnish can be clear or stained, mat or gloss or, if desired, the whole floor can be changed to an oiled finish!

Maintenance

A lacquer soap or floor polish, either diluted in water or ready to use, not only cleans the varnished surface, but it actually strengthens the lacquer as it protects against wear and scratches and thereby prolongs the lifetime of the lacquered surface. Application as required.

Please use floor protector underneath all furniture to avoid scratching.

Cleaning

Special cleaners are available for particularly stubborn stains such as grease, red wine, blood, coffee stains etc. Occasionally (about once a year depending on wear and tear) the floor can be buffed and recoated a full coating – see refurbishment section below. Avoid doing in sections at the appearance will vary between old and new areas.

NB! Water can damage a wooden floor! Clean wooden floors with minimum quantity of water using a micro fibre mop, especially in the case of engineered flooring.

Refurbishment

Slightly worn areas where only the top layer has been affected can be redone with a 2-component varnish from specialized manufactures (see Loba.com or Bona.com) Please only use experienced floor sanders to perform this job.

Warranty Details

- Normal and reasonable wear and tear of the flooring is not covered by our warranty
- Fading of stains and normal wearing of protective coats is not covered by our warranty
- Sub-standard installation is not covered under the warranty
- We cannot be held responsible for an inadequate sub-structure of the base upon which our product is laid.
- Water or moisture damage is not covered under the warranty and is null and void