

E C O  O A K
F L O O R I N G

4

INSTALLATION GUIDE:
UV OILED WOOD
FLOORING

INSTALLATION GUIDELINES FOR UV OILED WOODEN FLOORS

The product has a hard wax oil finish that is UV treated, directly after its application in the factory process. The UV treatment, creates a set and cured film on the surface of the board, which makes it differ from a hand applied hard wax oil. This film firstly gives the finish further strength to withstand the day to day usage on the installed floor, along with it not requiring a further coat of oil/hard wax oil upon completion of the floors installation. The product should not be over-coated but only maintained until the finish is in need of a renovation.

Protecting UV Oiled floors

Dirt, grit and abrasive particles which come in contact with the floor can reduce the lifecycle of the UV coating. Scratches form and dulls the surface of the wood. Floor rugs can be placed at all entrances, this is an effective way to prolong the surface coating. The underside of standing furniture, should be applied with furniture feet to protect the floor finish.

Regular maintenance

The following information is designed as a guide. It's important to note that all floors are unique and therefore each floor requires individual assessment. Changes in traffic levels and seasonal changes will need to be considered. The regularity of floor maintenance should reflect the use of the floor, and should be made accordingly.

Soluble dirt should be removed by using a micro fibre mop. A cleaning solution specially made for UV oiled wooden floors must be used. (See Loba.com and Bona.com for more information on cleaning products for UV oiled flooring)

Changing the colour

In order to change the colour of the floor you will need to sand down the floor to the original colour. This process is very technical so we suggest contracting in only qualified tradesman to perform this work. Always ensure you are happy with your sample before going ahead with the finishing.

Warranty Details

- Normal and reasonable wear and tear of the flooring is not covered by our warranty
- Fading of stains and normal wearing of protective coats is not covered by our warranty
- Sub-standard installation is not covered under the warranty
- We cannot be held responsible for an inadequate sub-structure of the base upon which our product is laid.
- Water or moisture damage is not covered under the warranty and is null and void